



NOTE:

1. THE 17.0m ROW IS PERMITTED ONLY WHERE APPROVED BY TOWN
2. ALTERNATIVE UTILITY LOCATION SUBJECT TO TOWN APPROVAL.
3. REFER TO DESIGN CRITERIA SECTION B FOR PAVEMENT DESIGN REQUIREMENTS.
4. BOULEVARD WITH SIDEWALK TO BE LOCATED AS DIRECTED BY THE TOWN ENGINEER.

MINIMUM PAVEMENT DESIGN

ASPHALT - 40mm HL3 SURFACE
50mm HL8 BINDER

MINIMUM GRANULAR
BASE COURSE - 150mm GRANULAR 'A'
300mm GRANULAR 'B'

SELECT SUBGRADE MATERIAL AS REQUIRED
EARTH MATERIAL SUB-GRADE COMPACTED TO 95% OF
MAXIMUM DRY DENSITY AS PER OPSS 501.08.02

<p>THE CORPORATION OF THE TOWN OF AJAX</p>		<p>ENGINEERING SECTION</p>	
<p>APPROVED COUNCIL</p>	<p>8.5m LOCAL ROADWAY 17.0m RIGHT-OF-WAY</p>		<p>DWG. No.</p>
<p>REVISION No.</p>			<p>AS-205</p>
<p>DATE 2002</p>			